



HER

1 phase in / 1 phase out

6 - 10 - 15 kVA

PROLOGIC 100D SERIES

ON-LINE DOUBLE CONVERSION UNINTERRUPTIBLE POWER SUPPLIES

IGBT RECTIFIER DSP CONTROL

Prologic 100 D Series UPS

*are single phase in/single phase out, IGBT rectifier,
Intelligent Power Module technology based, high
input power factor, low THDI and DSP controlled.*

GENERAL SPECIFICATIONS

- Transformerless UPS topology
- IPM power module
- High input power factor > 0,98
- DSP controlled system
- Full digital control system
- Tower and rack type options
- PID control system
- Low input current value (THDI < 5%)
- High efficiency (up to 93%)
- Cold start function
- Static by-pass system
- Optional maintenance by-pass switch
- Optional split by-pass system
- VAT transfer (voltage adaptive transfer)
- Output overload and short circuit protection
- External REPO input
- 128 events (5000 alarms) memory
- Clock, calendar and operating hourmeter
- Advanced automatic battery test
- Boost charge system
- Temperature compensated charge system
- RS232 port and dry contact relays
- Easy output voltage and frequency selection
- Optional SNMP adaptor
- Manufactured according to EC Directive; EN62040
- 10 years spare parts support
- 2 years warranty



CE



HOLLROM CONSULTING & TRADING S.R.L.

address: 15B Bratului street, 020565 Bucharest, Romania,
office@hollrom.ro, www.hollrom.ro, Tel: +40 21 210 83 85,
+40 743 338 442, +40 747 359 366, Fax: +40 21 210 83 85



6 - 10 - 15 kVA

TECHNICAL SPECIFICATIONS



MODEL	Prologic106D	Prologic110D	Prologic115D		
Power (kVA)	6	10	15		
INPUT					
Voltage	220/230 VAC 1P + N + G				
Input voltage range	170 - 275 VAC				
Frequency	50Hz / 60Hz				
Frequency range	40Hz - 65Hz				
Power factor (at 100% load)	> 0,98				
THDI (at 100% load)	< 5%				
By-pass voltage / frequency	220/230 VAC ± 10%, 50Hz / 60Hz				
By-pass frequency tolerance	Adjustable (for synchronization)				
Split by-pass connection	Optional				
OUTPUT					
Power (kW)	4,2	7	10,5		
Voltage	220/230 VAC 1P + N, ± %1				
Frequency	50Hz / 60Hz				
Frequency tolerance	Line synchronized: ± 1% / Free running: ± 0,1%				
Efficiency	Up to 92%				
Crest factor	3:1				
Voltage THD	< 3% (linear load) < 5% (non-linear load)				
Overload protection	100% - 125% load 10 min, 126%-150% load 1 min, >150% load: by pass				
Connections	Hardwired + 2 x IEC sockets on the rear (Optional)				
BATTERIES					
Type	Sealed Lead Acid-Maintenance free				
Number of batteries	20x12V standard (16 to 24 selectable)				
Float charging voltage(adjustable)	270 VDC (20x12V for battery)				
End of discharge voltage(adjustable)	200 VDC (20x12V for battery)				
Battery housing	Internal	External Cabinet			
Battery ambient temperature	25°C				
Boost charge	Available				
Battery test	Automatic or Manual, available				
GENERAL					
Standards	EN62040-1, EN62040-2				
Communication	RS232 standart-RS485 optional				
Software	Standard T-Mon UPS Management Software (3 clients + 1 server management)				
Alarm relays	3 standard (+2 programmable optional)				
Remote EPO input	Available as standard				
Operating temperature	0°C - 40°C				
Storage temperature	-10°C to 50°C				
Protection degree	IP20				
Relative humidity	< 90% (non-condensing)				
Altitude	< 2000m. above sea level				
Acoustic noise	< 50 dBA				
Weight without batteries (kg)	23	39	40		
Dimensions (mm) HxWxD	430x215x600	590x215x780			
	430x600x215 (19"rack version)				
OPTIONS					
Different input / output voltage	Please ask				
Transformer	Galvanic isolation transformer				
Adaptors	SNMP, RS485, Remote panel, MODBUS (RS485!TCP/IP)				
Parallel operation	Upon request				