

# AAP-4200 DE

Engine : Aksa  
Alternator : Aksa



**SZUTEST**

This generator set is manufactured in facilities certified to ISO 9001.

**CE**

This generator set is available with CE certification.

## 1 Phase Ratings, 50 Hz, PF 0,0

Voltage	Standby Rating (ESP)		Prime Rating (PRP)		
	kVA	kW	kVA	kW	Amp
230	5,00	4,50	4,50	4,20	18,00

**Standby Rating (ESP):** Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528. Overload is not allowed.

**Prime Rating (PRP):** Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046.

## OPTIONAL EQUIPMENTS

ENGINE

OTHER ACCESSORIES

ALTERNATOR

CONTROL SYSTEM

TRANSFER SWITCH  
- On request (optional)

# AAP-4200 DE

Engine : Aksa  
Alternator : Aksa

## ● DIESEL ENGINE SPECIFICATIONS

Manufacturer		Aksa
EU Stage		II
Total Displacement	L	406,000
Rated Speed (rpm)	rpm	3000
Governor		Mechanical
Oil Capacity	L	1,65
Start System		12 V d.c.
Fuel Consumption	Load	%100
	L/h	1,33

## ● ALTERNATOR SPECIFICATIONS

Make		Aksa
Frequency	Hz	50
Design		Brushless, 2 poles
Phase		1
Voltage	V	230
Insulation Class		H

## ● DIEMENSIONS AND WEIGHT

Open Type	Dry Weight	Lenght	Width	Height	Tank Capacity
	kg.	mm.	mm.	mm.	L
AAP-4200 DE	186,00	520,00	920,00	700,00	16,00