

# AAP-4200 DE

Engine : Akxa  
Alternator : Akxa



**SZUTEST**

Produs in fabrica agreata ISO 9001.



Disponibil cu certificare CE.

**Specificatii (monofazic), 50 Hz, FP 0,8**

Tensiune	In asteptare (ESP)		Sursa Primara (PRP)		
	kVA	kW	kVA	kW	Amp
230	5,00	4,50	4,50	4,20	18,00

In asteptare (ESP):

Aplicabil in alimentarea mai multor tipuri de consumatori, esentiali pe perioada intreruperii de curent. Nu se permite suprasarcina

Prime Rating (PRP):

Aplicabil in alimentarea mai multor tipuri de consumatori pe o perioada nelimitata. PRP se afla in concordanta cu ISO 8528. Se permite suprasarcina de 10% pe o perioada de 1 ora din 12 ore de functionare, in acord cu ISO 304

- AUTOMATIZARE DE TRANSFER (AAR)

La cerere (optionala)

# AAP-4200 DE

Engine : Aksa  
Alternator : Aksa

## 1 SPECIFICATII MOTOR DIESEL

Producator		Aksa
Clasificare EURO		II
Cilindree totala	L	406,000
Turatie	rpm	3000
Regulator de turatie		Mechanical
Capacitate ulei	L	1,65
Sistem de pornire		12 V d.c.
Consum de combustibil	Load	%100
	L/h	1,33

## 2 SPECIFICATII ALTERNATOR

Model		Aksa
Frecventa	Hz	50
Constructie		Fara perii, 2 poli
Faze		1
Tensiune	V	230
Clasa de izolatie		H

## 3 DIMENSIUNI SI GREUTATE

Deschis	Masa fara lichide	Lungime	Latime	Inaltime	Capacitate rezervor
	kg.	mm.	mm.	mm.	L
AAP-4200 DE	186,00	520,00	920,00	700,00	16,00