

APD 150 A

Engine : Aksa
 Alternator : Aksa
 Control System : P 602



ISO8528

This generator set has been designed to meet ISO 8528 regulation.

SZUTEST

This generator set is manufactured in facilities certified to ISO 9001.



This generator set is available with CE certification.

2000/14/EC

Enclosed product is tested according to EU noise legislation 2000/14/EC

3 Phase Ratings, 50 Hz, PF 0,8

Voltage	Standby Rating (ESP)		Prime Rating (PRP)		
	kVA	kW	kVA	kW	Amp
400/230	150,00	120,00	137,00	110,00	197,00

Standby Rating (ESP): Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528. Overload is not allowed.

Prime Rating (PRP): Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046.

STANDARD SPECIFICATIONS

- Heavy duty, water cooled diesel engine
- Radiator with mechanical fan
- Protective grille for fan and rotating parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine jacket cooling heater
- Steel base frame and anti-vibration isolators
- Spare Fuel Tank
- Flexible fuel connection hoses
- Two bearing, class H alternator
- Industrial exhaust silencer and steel belows supplied separately
- Static battery charger
- Manual for use and installation

OPTIONAL EQUIPMENTS

ENGINE

- Oil heater

ALTERNATOR

- Anti-Condensation Heater
- Main line circuit breaker

CONTROL SYSTEM

- Earth fault, single set
- Charge Ammeter

OTHER ACCESSORIES

- Automatic or manual fuel filling system
- Manual oil drain pump
- Low and high fuel level alarm
- Enclosure: weater protective or sound attenuated
- Trailer
- Tool kit for maintenance
- Main Fuel Tank

TRANSFER SWITCH

- Three Pole Contactor
- Four Pole Contactor
- Motor Switch

APD 150 A

Engine : Akxa
Alternator : Akxa
Control System : P 602



➤ DIESEL ENGINE SPECIFICATIONS

Manufacturer		Akxa
Model		A6CRX69TI
No. of Cylinders and Build		6 Cylinder, In Line
Aspiration and Cooling		Turbo Charged and After Cooled
Maximum Standby Power		1500 rpm
		138,00 kW [185,00HP]
Total Displacement	L	6,870
Bore and Stroke	mm	108 x 125
Compression Ratio		17:1
Rated Speed (rpm)	rpm	1500
Governor		Electronic
Oil Capacity	L	16,00
Coolant Capacity	L	30,00
Intake Air Flow	m ³ /min.	11,00
Radiator Cooling Air	m ³ /min.	153,00
Exhaust Gas Flow	m ³ /min.	29,00
Start System		24 V d.c.
Fuel Consumption	Load	%100
	L/h	32,50

➤ ALTERNATOR SPECIFICATIONS

Make		Akxa
Frequency	Hz	50
Design		Brushless, 4 poles
Cos Phi		0,80
Phase		3
Voltage	V	400/230
Current	A	0,00
Insulation Class		H

➤ DIEMENSIONS AND WEIGHT

Open Type	Dry Weight	Lenght	Width	Height	Tank Capacity
	kg.	mm.	mm.	mm.	L
APD 150 A	1590,00	2400,00	1100,00	1620,00	350
Canopy	Dry Weight	Lenght	Width	Height	Tank Capacity
	kg.	mm.	mm.	mm.	L
APD 150 A	2020,00	3270	1170	1870	350

APD 150 A

Engine : Akxa
Alternator : Akxa
Control System : P 602



1 P 602 - Control System



- 1 A U]b'gHh g'X]gd'Um'
- 2 8]gd'Um]gVc''Vi Hrcb''
- 3 DU[Yf]bZcfa U]jcbE'Vi Hrcb''
- 4 7 ca a cb U'Ufa]bX]W]rcf''
- 5 GHh g'@98fj''
- 6 C dYfU]jcb'gY'YV]b['Vi Hrcbg''

2 Devices

8G9ža cXY''\$\$'5i hc'A U]bg:] U]i fy Věbfc''a cXi 'Y''
6UHYfmVUf[Yf]bdi h%, !&* ('j c'hžci rdi h''&+ž' 'j) '5'f&('j E'cf%' ž 'j c'h) 5'f&& ž
9a Yf[YbVhrcd'di g\ 'Vi Hrcb'UbX ž gYg'Z'fVěbfc''V]fV]rg''

3 Construction and Finish

7 ca dcbYbrj]bgU''YX]b'g\YYhg''YbWc]i fy''D\cgd\UHY'WYa]W'ždfY!VěU]b['cZghY''dfcj]XYg Věffcg]cb
fyg]g]Ubhgi fZUW''Dc'mYgYfVěa dcm]Y' dck XYf'rcdVěU]hZcfa g\]] ['cgg'UbX'Yi HYa Y'mXi fUV'Y ž]b]g\''@cV]UV'
UbX\]b[YX'dUbY'Xccf'dfcj]XYg YUgmUWV]gg'hc''Věa dcbYbrj''

4 Installation

7 cblfc'dUbY'']g'a ci bHYX'cb VUgYZUa Y'k]h' gHY''g]UbX''@W]HYX'Uhih'Y'f[\hig]XY'cZh'Y [YbYfU]rcf'gYhfK \Yb'mci
'cc_'Uhih'Y; Yb''GYH'Zca '5'HYfbU]rcfE

5 Generating Set Control Unit

H\Y''8G9''\$\$']g'U'g]UbXUfX Věbfc''a cXi 'Y'Z'f'ci f [YbYfU]rcf'gYhg'i d'hc'&\$\$_j 5'UbX'ih\Uj Y'VYYb'XYg][bYX'hc
g]U]f]h'UbX'ghrcd'X]YgY' UbX' [Ug[YbYfU]rcf'gYhg''H\Y'8G9''\$\$' a cXi 'Y'Ug'VYYb'XYg][bYX'hc'a cb]rcf [YbYfU]rcf
Z]Yei YbVhžj c'iz'W'fYb]hžYb[]bY'c']dfYggi fyžVěc'UbhiYa dYfU]h'fy'fi bb]b[\ci fg'UbX' VU]HYfmj c'lg''A cXi 'Y
a cb]rcf'g'h'Y'a U]bg'gi dd'm]UbX'gk]H\W'c] Yf'hc'h'Y [YbYfU]rcf'k \Yb'h'Y'a U]bg'dck Yf'ZU]g''H\Y'8G9''\$\$' U'gc
]bX]W]HYg'cdYfU]jcbU'g]U]h'g'UbX'Z]i 'hVěbX]h]cbgž'5i hca U]h]W'm]g\i H]b['Xck b'h'Y; Yb''GYhUbX' []]b['Hfi Y'Z]fghi d
Z]i 'hVěbX]h]cb'cZ; Yb''GYhZ]i' fy'H\Y'@78'X]gd'Um]bX]W]HYg'h'Y'Z]i 'H'

Standard Specifications

A]VědfcW'ggcf Věbfc''YX''
@78'X]gd'Uma U_Yg]bZcfa U]jcb YUgm]rc'fYUX''
(!']bYž*('1' % &d]]Y'X]gd'Um'

5i hca U]h]W'm]f]UbgZ]fg'VYh'YYb'a U]bg'fi H]h]rc'UbX' [YbYfU]rcf'dck Yf''
A Ubi U'dfc[fUa a]b['cb'Z'cbhdUbY''
I gYf]Z]YbX'm]gYH'i d'UbX'Vi Hrcb''U]rci H'
: fcbhdUbY'dfc[fUa a]b[''
FYa cHY'g]U]fH'

9j Ybh'c[[]b['f]g]g\ck]b['XU]Y'UbX'h]a Y''
7 cblfc'g' Ghrcd#F'YgYh]A Ubi U'ž'5i hcžHYghZ'GHU]f]Z'Vi Hrcbg''5b'UXX]h]cbU'di g\ 'Vi Hrcb'bYi hrc'h'Y'@78'X]gd'Um]g
i gYX'hc'g]Vc''h'fci [\h'Y'a cXi 'Y'g]fa YH'f]b['X]gd'Um]g''

APD 150 A

Engine : Aksa
 Alternator : Aksa
 Control System : P 602



Instruments

9B: #9
 9b[]bY'gdYYX"
 C]'dfYggi fY"
 7cc'UbhY'a dYfUhi fY"
 F i b' hja Y"
 6UHYfmj c'rg"
 7cbZ[i fUVY' hja]b["
 ; 9B9F5HCF
 J c' hU[Y f@ @B' "
 7i ffYbhf@ @& @ E"
 : fYei YbVW"
 A5-BG
 J c' hU[Y f@ @B' "
 : fYei YbVW"
 A U]bg'fYUXn'
 A U]bg'YbUV'YX"
 ; Yb"GYhfYUXn'
 ; Yb"GYhYbUV'YX"

Protection Circuits

K 5F B-B;
 7\Uf[Y Z]i fY"
 6UHYfm@ck # [\] c' hU[Y"
 : U] 'hc' ghcd"
 @ck # [\ [YbYfUhc'f j c' hU[Y"
 I bXYf#j Yf [YbYfUhc'f ZYei YbVW"
 Cj Yf# bXYf'gdYYX"
 @ck c]'dfYggi fY"
 <] \ V'c' UbhY'a dYfUhi fY"
 G<I H8CK BG
 : U] 'hc' ghUff"
 9a Yf [YbVW'ghcd"
 @ck c]'dfYggi fY"
 <] \ V'c' UbhY'a dYfUhi fY"
 Cj Yf# bXYf'gdYYX"
 I bXYf#j Yf [YbYfUhc'f ZYei YbVW"
 I bXYf#j Yf [YbYfUhc'f j c' hU[Y"
 C]'dfYggi fY'gYbgcf'cdYb"
 7cc'UbhY'a dYfUhi fY'gYbgcf'cdYb"
 9@97 HF =75@HF -D
 ; YbYfUhc'f c j YfW ffYbh'

Options

: 'YI J'Y'gYbgcf'WVb VY V'c' bfc' 'YX' k]h' h'Ya dYfUhi fYz
 dfYggi fYz dYfVW'bhU[Y f'k Ufb]b[#] \ i f'Xck b# 'YVW'VW' f'f'dL
 @c'W' gYh]b['dUfUa YHfg'UbX'a cb]hc'f]b['Zca 'D7' hc
 V'c' bfc' 'a cXi 'Y' k]h' I G6 V'c' bbYVW'cb' f'a Ul '* 'a H'

Standards

9'YVW'VW' 'GUZY'hm#9A 7 'V'c'a dUfV']hm6G'9B '* \$-) \$
 9'YVW'VW' 'Vi g]bYgg' 'Yei]da Ybh'
 6G'9B '*%\$ \$! *! & 9A 7 'ja a i b]mighUbxUfX"
 6G'9B '*%\$ \$! *! ('9A 7 'Ya jgg]cb' ghUbxUfX"

Static Battery Charger

'6UHYfmVUf[Yf]g'a Ubi ZVW' fYX' k]h' 'gk]h'W]b[!a cXY'UbX'GA 8 'fVW'bc'c[mUbx'ih\Ug\] [\ YZ]VbYVW' 6UHYfmVUf[Yf
 a cXY'gfci hdi hJ !=VUfUWV'f]gh]W]g'j YfmV'cgY'hc'gei UfY'UbX'ci hdi h]g'] 'Ua dYfz% z 'J 'Zcf'%&j'c'hUbX' &+Z' 'J 'Zcf'&'('J '
 #bdi h% , ' ! &* (j c'h57 "' Dfc']bY' &(\$) \Ug'Z' 'mici hdi hg\chV'fVW]hdfchV'W]cb'UbX'ihVWb'VY' i gYX'Ug'U'VW'ffYbhgci fVW"
 Dfc']bY' %&\$) #&(\$) 'VXUf[Yf'\Ug'\] [\ YZ]VbYVW'cb[']Z'Z' 'ck ZU]i fY'fUfYz'] [\ hk Y] [\ hUbX' 'ck \ YUhfUX]UfYX']b
 UVW'cfXUbVW' k]h' ']bYUf'U'fYfbU]j Yg' H\Y' VUf[Yf]g' Z]h'YX' k]h' 'U'dfchV'W]cb'X]cXY'UV'cgg'h'Y'ci hdi h'7 cbbYVW'VUf[Y'Z]
 fY'UmV'c'] VYhk YYb'dcg]h]j Y'ci hdi hUbX'7: 'ci hdi h' H\Y'mUfY'Yei]ddYX' k]h' F: =Z]h'f'hc' fYXi VV'Y'YVW'VW' 'bc]gY'fUX]UfYX
 Zca 'h'Y'XY' jVW"; Uj Ub]W' m]gc'UfYX']bdi hUbX'ci hdi h]hd]VW' m(_J 'Zcf'\] [\ fY']UV']h'f'

APD 150 A

Engine : Akxa
 Alternator : Akxa
 Control System : P 602



APD 150 A - Canopy

Introduction

Sound-attenuated and weather protective enclosures for generating sets from Akxa, meet even the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies (8 - 275kVA) fit directly to the open generator set to provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.



Standard Specifications

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and base-tank are pre-assembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Fuel fill and battery can only be reached via lockable access doors.

Lifting points on the top of canopy and base frame

Customer options available to meet your applications needs.

Width	mm.	1170
Length	mm.	3270
Height	mm.	1870