

# APG 62

Engine : PSI - GM  
 Alternator : Mecc Alte  
 Control System : P 732 control system



## ISO8528

This generator set has been designed to meet ISO 8528 regulation.

## SZUTEST

This generator set is manufactured in facilities certified to ISO 9001.



This generator set is available with CE certification.

## 2000/14/EC

Enclosed product is tested EU noise legislation 2000/14/EC

### Rated Power, 3 Phase, 50 Hz, PF 0,8

Voltage	Standby Rating (ESP)		Prime Rating (PRP)		
	kVA	kW	kVA	kW	Amp
400/230	62.00	48.00	54.00	43.00	78.50

#### Standby Rating (ESP):

Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528. Overload is not allowed.

#### Prime Rating (PRP):

Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046.

### Standart Specification

- Heavy duty, water cooled naturalgas engine
- 46/50 °C ambient rated radiator with mechanical fan
- Protective grille for fan and rotating parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine jacket cooling heater
- Base frame design incorporates an integral fuel tank and anti-vibration isolators
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel belows supplied separately
- Static battery charger
- Manual for use and installation

### Optional Equipments

#### ENGINE

- Remote Radiator Cooling
- Low Coolant level alarm

#### ALTERNATOR

- Anti-Condensation heater
- Over sized alternator
- Main line circuit breaker

#### WISE ACCESSORIES

- Manual oil drain pump
- Electrical oil drain pump
- Enclosure: weater protective or sound attenuated
- Duct adapter ( on radiator)
- Inlet and outlet motorised louvers
- Tool kit for maintenance
- Supplied with oil and coolant - 30 °C
- Automatic transfer switch

#### CONTROL SYSTEM

- Remote annunciator panel
- Alarm output relays
- Earth fault, single set
- Charging ammeter

# APG 62

Engine : PSI - GM  
 Alternator : Mecc Alte  
 Control System : P 732 control system

## ● Natural Gas Powered Engine Specification

Manufacturer	PSI - GM	
Model	5,7 L	
No. of Cylinders and Build	8 Cylinder V Type	
Aspiration and Cooling	Naturally Aspirated	
Maximum Standby Power	1500 rpm	49.0kW[HP]
Total Displacement	L	5.700
Bore and Stroke	Bore and Stroke	101,60 x 88,39
Compression Ratio	9,4:1	
Rated Speed	rpm	1500
Governor	Electronic	
Fuel Consumption	m <sup>3</sup> /h	15
Gas Pressure	mbar	27-300
Oil Capacity	L	4,7
Water Capacity	L	20
Exhaust Gas Flow	m <sup>3</sup> / min.	11
Exhaust Gas Temperature	° C	480
Electricity System	12 Vdc	

## ● Alternator Specification

Manufacturer	Mecc Alte	
Model	ECP32 2M/4B	
Power	kVA	63
Design	Brushless, 4 poles	
Cos fi	0,80	
Phase	3	
Voltage	V	400/230
5_ia	A	81
Stator	2 / 3 steps	
Excitation System	Electronic ( AVR )	


## ● Diemensions and Weight

Open Type	Dry Weight	Lenght	Width	Height
	kg.	mm.	mm.	mm.
<b>APG 80</b>	850	2200	1100	1300
Canopy	Dry Weight	Lenght	Width	Height
	kg.	mm.	mm.	mm.
AK 40	1050	3100	1050	1641

# APG 62

Engine : PSI - GM  
 Alternator : Mecc Alte  
 Control System : P 732 control system

## • P 732 control system - Control System



- 1 Menu navigation buttons
- 2 Close mains button
- 3 Main Status and instrumentation display
- 4 Alarm LED's
- 4 Close generator button
- 5 Status LED's
- 6 Operation selecting buttons

## • Devices

DSE, model 7320 Auto Mains Failure control module  
 Static battery charger  
 Emergency stop push button and fuses for control circuits

## • Structure And Paint

Comonents installed in sheet steel enclosure. Phosphate chemical, pre-coating of steel provides corrosion resistant surface  
 Polyester composite powder topcoat forms high gloss and extremely durable finish  
 Lockable hinged panel door provides for easy component access

## • Montage

Control panel is mounted generating set baseframe on robust steel stand or power module.  
 Located at side of generating set with properly panel visibility.

## • Generator Control Unit

The DSE 7320 control module is a standard addition to our generator sets from 220 kVA upwards and it has been designed to start and stop diesel and gas generating sets that include electronic and non electronic engines. The DSE 7320 includes the additional capability of being able to monitor a mains (utility) supply and is therefore suitable for controlling a standby generating set in conjunction with an automatic transfer switch. The DSE 7320 also indicates operational status and fault conditions, automatically shutting down the generating set and indicating faults by means of its LCD display on the front panel.

Microprocessor controlled  
 132 x 64 pixel LCD display makes information easy to read  
 Front panel programming and also via PC software  
 Soft touch membrane keypad and five key menu navigation  
 Remote communications via RS232, RS485 and ethernet and SMS messaging  
 Event logging (50) showing date and time  
 Multiple date and time engine exercise mode and maintenance scheduler  
 Engine block heater control.  
 Controls; stop, manuel, auto, test, start, mute lamb test/transfer to generator, transfer to mains, menu navigation.

# APG 62

Engine : PSI - GM  
 Alternator : Mecc Alte  
 Control System : P 732 control system

## Indicator

- ENGINE
- Engine speed
- Oil pressure
- Coolant temperature
- Run time
- Battery volts
- Engine maintenance due
- GENERATOR
- Voltage (L-L, L-N)
- Current (L1-L2-L3)
- Frequency
- Earth current
- kW
- Pf
- kVAr
- kWh, kVAh, kVArh
- Phase sequence
- MAINS
- Voltage (L-L, L-N)
- Frequency

## Protection

- WARNING
- Charge failure
- Battery under voltage
- Fail to stop
- Low fuel level (opt.)
- kW over load
- Negative phase sequence
- Loss of speed signal
- PRE-ALARMS
- Low oil pressure
- High engine temperature
- Low engine temperature
- Over /Under speed
- Under/over generator frequency
- Under/over generator voltage
- ECU warning
- SHUT DOWNS
- Fail to start
- Emergency stop
- Low oil pressure
- High engine temperature
- Low coolant level
- Over /Under speed
- Under/over generator frequency
- Under/over generator voltage
- Oil pressure sensor open
- Phase rotation
- ELECTRICAL TRIP
- Earth fault
- kW over load
- Generator over current
- Negative phase sequence

## Optional Properties

- High oil temperature shut down
- Low fuel level shut down
- Low fuel level alarm
- High fuel level alarm
- EXPANSION MODULES
- Editional LED module (2548)
- Expension relay module (2157)
- Expansion input module (2130)

## Standards

- Electrical Safety / EMC compatibility
- BS EN 60950 Electrical business equipment
- BS EN 61000-6-2 EMC immunity standard
- BS EN 61000-6-4 EMC emission standard


## Electronic Charge Equipment

6UHYfmVUf[ Yf]g'a Ubi ZVM fYX'k ]H'gk ]fV]b[ !a cXY'UbX'GA 8'fVWbc`c[ mUbX`ih\Ug`\[ \ YZ]V]bVWf  
 6UHYfmVUf[ Yf'a cXY`gfc i hdi hJ !=VUfUWVf]g]W]g] YfmVcgy`tc`gei UfY`&(\$)`Ug`Z`mci hdi hg`chV]V]hdfchV]cb`UbX  
 ihV]b`VY`i gYX`Ug`U`W`ffYbhgci`fV`  
 &(\$)`VUf[ Yf`Ug`\[ \ YZ]V]bV]cb[ ``ZY`ck`Z]i`fy`fU]z`][ \hk`Y][ \hUbX`ck` \YUhfUX`U]YX`]b`UW]cfXUbW`k`h` ``]bYUf  
 U`fYfbU]h] Yg`  
 H`Y`VUf[ Yf]g`Z]H`X`k`]H`U`dfchV]cb`X]cXY`UW]cgg`h`Y`ci`hdi`H`7`Uf[ Y`Z]`ci`hdi`h]g`U]U]UV`Y``7`cbbYV]VUf[ Y`Z]`fY`Um  
 V]`VY`k`YYb`d cg]h] Y`ci`hdi`hUbX`7`:`ci`hdi`H`  
 `bdi`h`%`\*!&\*(J`  
 C`i`hdi`h`&+z`J` `)5`cf`%`z`J` `)5`

# APG 62

Engine : PSI - GM  
 Alternator : Mecc Alte  
 Control System : P 732 control system

## AK 40 - Canopy



- 1 Steel structures
- 2 Emergency stop push button
- 3 Control panel is right side of the set.
- 4 Corrosion-resistant locks and hinges
- 5 Sump drains valves
- 6 Lockable, large doors o each side
- 7 Sound proof foam metarial
- 8 Base frame -tank
- 9 Lifting Points

## Introduction

Sound-attenuated and Weather-protective Enclosures Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

## Standart Specification

- Compact footprint, low profile design.
- Enclosure, generator set, exhaust system and fuel tank are pre-ssembled, pre-integrated and shipped as one package
- Body made from steel components treated with polyester powder coating
- Fire retardant foam insulation
- Easy access to all service points
- Exhaust system inside canopy
- Large doors on each side
- Control panel viewing window in a lockable access door
- Emergency stop push button mounted on enclosure exterior
- Cooling fan and battery charging alternator fully guarded
- Fuel fill and battery can only be reached via lockable access doors.
- Lifting points on the top of canopy and base frame
- Customer options available to meet your applications needs.
- Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level test has been approved by the notified body Szutest

Canopy Model		AK 40
Width	mm.	1050
Lenght	mm.	3100
Height	mm.	1641