

WATER COOLED



THREE PHASE



50 HZ



DIESEL

Generating Rates		PRIME	STANDBY
Power	kVA	259	285
Power	kW	207	228
Current	(cos Phi=0,8) A	373	411
Standard Voltage	V	400/230	
Revolution Per Minute	r.p.m.	1500	
Rated at power factor	Cos Phi	0,8	

Standard Features

- 4 Stroke, 1500 RPM, water cooled heavy duty diesel engine
- Protection system on manual run
- Flexible oil pipes and oil draining valve
- Pre-heater
- Lubrication oil and anti-freeze
- 4 Poles, synchronotype, single bearing, brushless alternator
- Batteries and cables
- Electrostatic paint coated, steel, welded chassis
- Fuel tank housed in the chassis
- Industrial type silencer
- Electronic battery charger
- Electrical wiring diagram
- User manual and operating manual

Optional Equipments

- Soundproof canopy
- Automatic transfer switch
- Circuit breaker
- Trailer
- External fuel tank
- Electronic governor
- Heating system for fuel tank
- Oil heater
- Fuel filling system (Automatic / Manuel)
- Analog indicators
- 1 Phase - 3 Phase switch plugs
- Alarm system for fuel level
- Remote control and monitoring

Stand By Power : Supplying of emergency electrical power at variable load, in the event of normal utility power failure. This rating is maximum power, no overload capability is available.

Prime Power : Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility power failure. 10% over load capability is available.

Engine Specifications

Brand		SDEC
Model		SC9D340D2
Engine Power Stand BY	(kWm / hp)	250/340
Revolution Per Minute	(r.p.m.)	1500
Total Displacement	(L)	8.82
Cylinders Orientation		6 V TYPE
Bore x Stroke	(mm x mm)	114 x 144
Compression Orientation		16,5:01
Governor Type		ELECTRONIC
Aspiration System		INTERCOOLER
Injection		DIRECT
Cooling		WATER COOLED
Electrical System	(VDC)	24
Lub-Oil Capacity	(L)	25
Engine Coolant Capacity	(L)	12
Fuel Tank Capacity	(L)	450
Maximum Exhaust Temperature	(°C)	600
Maximum Exhaust Gas Flow	(m3/H)	2460
Maximum Allowed Back Pressure	(kPa)	5
Cooling Air Flow	(m3/min)	1116
Fuel Consumption 50 %	(L/h)	27.3
Fuel Consumption 75 %	(L/h)	40.8
Fuel Consumption 100 %	(L/h)	54.1

- Replacable cylinder jacket
- Dry type replacable oil filter
- Heat-resistant radiator for 50 °C

Alternator Specifications

Output Voltage	(V)	400/230
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1 %
Short Circuit Current		> 300 %
Insulation		H
Protection		IP 23
Efficiency	(%)	93
Overloading		110 % FOR 1 HOUR
Power Factor	(cos Phi)	0.8
Total Harmonic Distortion Rate		THF < 2 %
Connection Type		STAR
Number Of Pole		4
Number Of Bearing		SINGLE

- 4 Poles, Self-Excitation, Brushless, Synchronotype alternator
- Electronic type automatic voltage regulator (AVR)
- Self-Cooled

Update Date : 27-02-16 14:02


KJS285ds-2

Dimensions Without Canopy

Dimensions and Weight		
Length (L)	mm	3000
Height (H)	mm	1900
Width (W)	mm	1400
Wet weight	kg	2550
Fuel Tank Capacity	L	450


Dimensions With Canopy

Dimensions and Weight		
Length (L)	mm	3900
Height (H)	mm	2350
Width (W)	mm	1400
Wet weight	kg	2850
Fuel Tank Capacity	L	450


Control Panel Features

- Diesel and gas genset support
- 400Hz operation support
- 400 event logs, full snapshot
- All parameters front panel editable
- 3 level configuration password
- 128x64 graphical LCD display
- Downloadable language
- Waveform display of V & I
- Harmonic analysis of V & I
- Synchroscope & check synch
- Allows closed transfers
- 16Amp MCB & GCB outputs
- 8 configurable digital outputs
- Outputs expandable to 40
- 4 configurable analog inputs
- Both CANBUS-J1939 & MPU
- 3 configurable service alarms
- Multiple nominal conditions
- Multiple automatic exerciser
- Weekly operation schedule
- Dual mutual standby with equal aging of gensets
- Manual "speed fine adjust" on selected ECUs
- Automatic fuel pump control
- Disable protections feature
- Excess power protection
- Reverse power protection
- Overload IDMT protection
- Load shedding, dummy load
- Multiple load management
- Current unbalance protection
- Voltage unbalance protection
- Fuel filling & fuel theft alarms
- Battery back-up real time clock
- Idle speed control
- Battery charge0 run enabled
- Combat mode support
- Contactor & MCB drive
- 4 quadrant genset power counters
- Mains power counters
- Fuel filling counter
- Fuel consumption counter
- Modem & Ethernet diagnostics
- Configurable through USB, RS-485, Ethernet and GPRS
- Free configuration program
- Allows SMS controls
- Ready for central monitoring Ethernet and GPRS
- Mobile genset support
- Automatic GSM geo-location
- GPS connectivity (USB & RS232)
- Dynamic DNS support
- Easy USB firmware upgrade
- IP65 rating with standard gasket

